



ALLIANCE | **CONSTRUCTION & INDUSTRIAL**

330

TRA: R-3 | Speed Rating: A8



SPECIAL COMPOUND



RESISTANT COMPOUND



HEAT & CHIP RESISTANT COMPOUND

TRACTOR HEAVY DUTY - 23.1-26

Size	Rim	Unloaded Dimension		Loaded Static radius mm	Rolling Circumference mm	Load Index PR Symbols	Inflation Pressure bar	Recommended Load									
								Speed									
		Drive wheel						Free rolling									
		10 kmph	25 kmph					40 kmph	50 kmph	Static kmph	10 kmph	25 kmph	40 kmph	50 kmph			
23.1-26	DW20	587	1580	697	4600	10PR	1.2	4540	3850	3630	3300	9200	5000	4240	4000	3640	
							158A8	1.3	4940	4190	3950	3590	9980	5430	4600	4340	3950
							1.4	5310	4510	4250	3870	10750	5840	4960	4675	4250	
						12PR	1.5	5510	4670	4410	4010	11180	6080	5150	4860	4420	
							162A8	1.6	5730	4850	4580	4170	11590	6300	5340	5040	4590
							1.7	5940	5040	4750	4320	12020	6530	5540	5225	4750	
		16PR	168A8	1.9	6260	5310	5010	4560	12670	6890	5840	5510	5010				
				2.1	6640	5630	5310	4830	13430	7300	6190	5840	5310				
				2.3	7000	5940	5600	5100	14170	7700	6530	6160	5610				
		18PR	170A8	2.4	7160	6070	5730	5210	14490	7880	6680	6300	5730				
				2.5	7330	6210	5860	5330	14840	8060	6840	6450	5870				
				2.6	7500	6360	6000	5460	15180	8250	7000	6600	6010				

Note: For above mentioned size 10 PR is no longer active for production.

For ATC Tires Pvt Limited

Vidit Jain



Vidit Jain
 Chief (Technology and R&D)

