



# APOLLO ALT 188

- **Double chevron non-directional tread pattern** to provide excellent longitudinal and lateral traction capabilities
- **Customized tread compound** for excellent performance in **varying mine conditions**
- **Wider grooves** towards the shoulder which **reduce the chances of stone entrapment**
- **Superior and enduring carcass for trouble free service** under extreme conditions

apollo





# ALT 188

# EARTHMOVE

Size	Ply Rating	Load Index	TRA Pattern Code	Type TT/TL	Unloaded Inflated Dimensions				Static Loaded Radius		Rolling Circumferences		Load Carrying Capacity (single Tyre)				TKPH		
					Section Width		Overall Diameter						Max Speed 50 Km/h (31 Mph)				Construction/Compound		
					mm	in	mm	in	mm	in	mm	in	mm	in	Load Index Speed Rating	Max Load Kg	Recommended Inflation pressure psi	bar	2A HR
-	-	-	-	-	mm	in	mm	in	mm	in	mm	in	-	Kg	psi	bar	-	-	-
21.00 -35	36	197	E4	TL	587	23.1	2066	81.3	966.9	38.1	6198	244.0	197 B	12850	80	5.5	275	200	170
	40	200	E4	TL	587	23.1	2066	81.3	966.9	38.1	6198	244.0	200 B	14000	90	6.2	290	215	190
24.00 -35	48	209	E4	TL	660	25.9	2180	85.9	1020.2	40.2	6540	257.5	209 B	18500	95	6.6	310	240	210
24.00 -49	48	215	E4	TL	655	25.8	2530	99.6	1184.0	46.6	7590	298.8	215 B	21800	95	6.6	360	295	255
	48	220	E4	TL	738	29.1	2695	106.1	1261.3	49.7	8085	318.3	220 B	25000	85	5.9	480	345	295
27.00 -49	54	223	E4	TL	738	29.1	2695	106.1	1261.3	49.7	8085	318.3	223 B	27250	95	6.6	510	375	320
	46	225	E4	TL	845	33.3	2910	114.6	1361.9	53.6	8730	343.7	225 B	29000	75	5.2	550	400	350
30.00 -51	52	226	E4	TL	845	33.3	2910	114.6	1361.9	53.6	8730	343.7	226 B	30000	80	5.5	570	410	360
	56	232	E4	TL	917	36.1	3052	120.2	1428.3	56.2	9156	360.5	232 B	35500	85	5.9	600	450	400
33.00 -51	60	244	E4	TL	1105	43.5	3566	140.4	1668.9	65.7	10698	421.2	244 B	50000	69	4.8	700	500	410
40.00 -57	68	247	E4	TL	1105	43.5	3566	140.4	1668.9	65.7	10698	421.2	247 B	54500	80	5.5	750	550	460

TT/TL - Tube Type & Tubeless

