





Benefits & Features:

- Hydraulic hose with swivel fitting and won't kink.
- Reinforced with 2 layers of braided steel
- All hoses can withstand extreme cold temperatures of -40°F (C).
 - Use with any 10,000 PSI pump, ram, or bead breaker

| Model # | Length | Attachments Included | Weight |
|---------|----------------|----------------------|---------------|
| 10603 | 8 ft. 96 in* | #10600 Coupler | 6 lbs. 3 kg |
| 10604 | 8 ft. 96 in* | #10605 Half Coupler | 5 lbs. 2.2 kg |
| 10610 | 8 ft. 96 in* | Hose Only | 4 lbs. 2 kg |
| 10611 | 18 ft. 216 in* | Hose Only | 9 lbs. 4 kg |

*8 ft. Hose with 3/8" 18 Male Ends

Hydraulic Couplers & Hydraulic Hoses

| #10600 | #10606 | #10605 | #10625 | #10626 |
|---|---|------------|--------|------------|
| Model # | Description | | | PSI Rating |
| 10600 Coupler Kit (High Flow) | Ram (female) Half #10606, Hose (male) Half #10605 (Interchangable with OTC, Power Team, Enerpac, and All ESCO Hydraulic Products. | | | 10,000 PSI |
| 10605 | Male Coupler with Female | 10,000 PSI | | |
| 10606 | Female Coupler with Male | 10,000 PSI | | |
| 10625 Quick Connect | Male Coupler with Female Tools) | 10,000 PSI | | |
| 10626 Quick Connect | Female Coupler with Female Threads (Parker Coupler interchangable with IMT Tools) | | | 10,000 PSI |