

# GALAXY HULK L-5



BACKHOE



SKIDSTEER

Galaxy Hulk has a unique tread pattern that allows it to operate in heavy duty applications while providing superior self-cleaning characteristics. The Hulk has a minimum tread depth of 44/32 NSD and a lug-to-void ratio of 68:32. As a result the Hulk provides long tread life and reduces downtime due to cuts and punctures.



HARD SURFACE



ON & OFF ROAD CONSTRUCTION



SEVERE CONDITION



Size	Type	PR	RIM	OD	SW	RC	SLR	Recommended Load	Inflation Pressure	Speed
				mm in	mm in	mm in	mm in	kg lbs	bar psi	kmph mph
10-16.5 NHS	TL	10	8.25	798.0	259.0	2337	366.0	2180	4.15	10
				31.4	10.2	92	14.4	4806	60	6
12-16.5 NHS	TL	12	9.75	838.0	307.0	2438	384.0	2575	4.5	10
				33.0	12.1	96	15.1	5677	65	6
14-17.5 NHS	TL	14	10.5	935	358	2743	427	3875	5.5	10
				36.8	14.1	108	16.8	8543	80	6
12.5/80-18 (320/80-18)	TL	14	9	965	305	2819	432	2000	4.3	40
				38.0	12.0	111.0	17.0	4409	62	25