

GALAXY SUPER TRAC E-3



Galaxy Super Trac is a premium all purpose tire for mining, industrial & port applications. Robust nylon casing & reinforced high strength bead provide excellent stability. Special tread compound provides extra long life even on abrasive surfaces. The tire has high ground contact area for good traction on paved surfaces. Continuous lug pattern helps to mitigate the chances of lug chunking and tire damage. The Super Trac has high lateral stability, enabling it to carry heavy load on concrete/hard surfaces. Extra thick side wall limits flexing during operation, thus lesser heat is generated. This reduces the probability of sidewall damage and results in longer service life of the tire.



HARD IMPROVED SURFACE



| Size | Type | PR | RIM | OD | SW | RC | SLR | Recommended Load | Inflation Pressure | Speed |
|-----------|------|----|-----------|------------------------------|-------|-------|-------|------------------|--------------------|----------|
| | | | | mm in | mm in | mm in | mm in | kg lbs | bar psi | kmph mph |
| 14.00-24 | TL | 28 | 10 | 1368 | 375 | 4090 | 630 | 13500 | 10 | 10 |
| | | | | 53.9 | 14.8 | 161.0 | 24.8 | 29762 | 145 | 5 |
| 14.00-24 | TT | 28 | 10 | 1368 | 375 | 4090 | 630 | 13500 | 10 | 10 |
| | | | | 53.9 | 14.8 | 161.0 | 24.8 | 29762 | 145 | 5 |
| 16.00-25 | TL | 32 | 11.25 | 1493 | 432 | 4460 | 686 | 16239 | 10 | 10 |
| | | | | 58.8 | 17 | 75.6 | 27 | 35801 | 145 | 5 |
| 16.00-25* | TL | 28 | | -----UNDER DEVELOPMENT ----- | | | | | | |
| 21.00-25 | TL | 40 | 15.00/3.0 | 1750 | 580 | 4915 | 820 | 27000 | 10 | 10 |
| | | | | 68.9 | 22.8 | 193.5 | 32.3 | 5952 | 145 | 5 |
| 21.00-35* | TL | 40 | | -----UNDER DEVELOPMENT ----- | | | | | | |